














Accessories

	Model	PEGA 15/35 Combination	Order No.	Price/€
	Measurement fitting DN 80/125 x DN 60/100	X	1004271	159.00
	Boiler connection fitting, concentric, DN80/125, straight type	X	1000361	56.40
	Boiler connection fitting, concentric, DN80/125, 87° Bend, H = 220 mm	X	1001918	91.00
	PEGA 40 ball valve connection set 3-way ball valve for simultaneous draining of the heater	X	1002526	117.87
	PEGA ball valve connection set as straight pattern type + drinking water approval	X	1002528	148.65
	NTC outdoor temperature sensor 10k	X	1003396	19.30

Accessories

	Model	Order No.	Price/€
	RSC-OT room unit The room unit offers plain text operation and room temperature measurement in one.	1001793	355.00
	CETA 104 Heating controller for single stage or modulating heating appliances (OpenTherm), direct heating circuit and hot water, incl. outdoor sensor and 2 boiler sensors	1001798	293.60
	CETA 106 Heating controller for mixer heating circuit differential temperature control, incl. outdoor sensor and flow sensor	1001799	272.00
	CETA 107 Heating controller for one-stage or modulating heating appliance OT-Bus, extension of mixed heating circuit and direct heating circuit, including flow sensor	1003456	550.00
	CETA RC EbV room remote control	1001756	164.80
	Hydraulic separator This hydraulic separator is matched to this PEGA: Size DN 80/120, nominal size DN40, connection sockets G 1 1/2", throughput 4 m³/h, Output 44 kW (at Dt =10 K), max. allowable operating temperature +110°C, minimum allowable operating temperature -20°C, max. allowable operating pressure 6 bar	1002678	475.00
	Magnetite filter 3/4"	1002677	215.00
	Inhibitor inhibits boiler scale and all types of corrosion 0.5 litre bottle is sufficient for 100 litre of heating water	1002676	47.70