

















Accessories

	Model	TANTUM 25 Heater	TANTUM 25 Combi	TANTUM 25 Compact 100	Order no.	Price/€
	Boiler fitting concentric, DN80/125, straight type	X	X	X	1000361	52.20
	Boiler fitting concentric, DN80/125, 87° elbow	X	X	X	1001918	84.00
	Fitting TANTUM Consisting of two corrugated pipes 340 mm, two reducers 3/4" – 1/2" and four gaskets 3/4"	X	X	—	1000411	67.50
	Ball valve fitting set TANTUM 3 way ball valve for simultaneous emptying of the heater	X	X	—	1002526	83.30
	Ball valve fitting set TANTUM as straight + drinking water approval	X	X	—	1002528	184.75
	Storage tank sensor – for the detection of the storage tank temperature	X	X	—	1001529	24.15
Necessary accessories for the time control of the heating system.						
	Room thermostat CMR 737 Installation in the living room. The heating operation is weather-compensated depending on the recorded room temperature. Room influence can not be switched off.	X	X	X	1003516	145.00
	Room thermostat T1 (analogue), 4 adjustable temperature levels, optional remote control via telephone, frost protection function. Installation in the living room. Heating operation is done by fixed value depending on the recorded room temperature. Room influence can not be switched off.	X	X	X	1002604	198.00
	Room unit RSC-OT The room unit offers plain text operation and room temperature recording in one. Installation near to the gas-condensing device in the boiler room is possible. Room temperature influence can be switched on and off.	X	X	X	1001793	350.00

Accessories

	Model	TANTUM 25 Heater	TANTUM 25 Combi	TANTUM 25 Compact 100	Order no.	Price/€
	CETA 104 Heating controller for single-stage or modulating heat generators (OpenTherm), direct heating circuit and hot water, incl. outdoor sensor and 2 boiler sensors	X	X	X	1001798	285.00
	CETA 106 Heating controller for mixer heating circuit Differential temperature control, incl. outdoor sensor and flow sensor	X	X	X	1001799	263.25
	CETA 107 Room unit OT bus, expansion of mixed heating circuit and direct heating circuit, including pre-flow sensor	X	X	X	1003456	527.65
	Hydraulic separator TANTUM This hydraulic separator is adjusted to the following TANTUM: Size DN 80/120, nominal size DN40, connecting socket G 1 1/2", flow rate 4 m³/h, capacity 44 kW (for Dt =10 K), max. permissible operating temperature +110°C, minimum permissible operating temperature -20°C, max. permissible operating pressure 6 bar	X	X	—	1002678	461.90
	Magnetic filter 3/4"	X	X	X	1002677	215.00
	Inhibitor, inhibits boilers and corrosion of all types, 0,5 l bottle is sufficient for 100 l heating water	X	X	X	1002676	46.30
	Cleaner for heating systems, for the commissioning of new systems or as a sludge cutter, 0,5 l bottle is sufficient for 100 l heating water	X	X	X	1002675	49.60